

HI-TEMP BUMPERS



DIMENSIONS

Diameter: 450 mm \pm 3 mm.

In accordance with IWF standards.

Widths: 90 mm (25 kg) | 80 mm (20 kg) | 70 mm (15 kg) | 56,5 mm (10 kg) | 31,5 mm (5 kg)

Tolerance: \pm 2 mm.

Depending on width and color:

WEIGHT

Red – 90 mm (25 kg) | **Blue** – 80 mm (20 kg) | **Yellow** – 70 mm (15 kg) | **Green** – 56,5 mm (10 kg) | **Gray** – 31,5 mm (5 kg)

Tolerance: \pm 1%.

FEATURES

Composition: Quality vulcanized recycled rubber discs. In the center rings with galvanized stainless steel.

Falls: 30.000 cycles

Durometer: Shore 75

Colors: Black with red, blue, yellow, green and gray grains.

Properties: Impact Absorption, Painless.

Easy placement and removal on equipment.

Sold individually.

FUNCTION

Used to add external load, usually in symmetry, to any equipment or bar. They can also be used solo in certain exercises.

MAINTENANCE

It is recommended to be used on a minimum 15mm impact absorption floor for durability. Mandatory use of springs to hold the bumpers.

For end consumers: 3 years.

For business consumers: 1 year.

WARRANTY

Exclusion of warranty: When misuse is verified. The 5kg bumpers must not be dropped from any height to the ground. The 10kg bumpers must not be dropped from above the waist. It must not fall on rubber flooring, or another floor or fall-arresting product less than 15mm. When proper cleaning and maintained is not carried out as described in the maintenance point.